

Single-phase
String Inverter

X1-Smart



Powerful Single Phase Inverter

Low Start-Up Voltage

High Efficiency

Flexible Communication

Remote Monitoring

X1-SMART (6.0kW / 7.0kW / 8.0kW)

- Remote upgrade and maintenance
- 150% DC oversizing and 110% AC overloading
- Support Meter/CT and zero injection control
- Small and compact size
- Easy to install and setup
- Support EV Charger





X1-SMART (SINGLE-PHASE)

X1-6.0-T-D**X1-6.0-T-N****X1-7.0-T-D****X1-7.0-T-N****X1-8.0-T-D****X1-8.0-T-N****DC INPUT**

Max. PV array input power [Wp]	3000/6000	3500/7000	4000/8000
Max. PV input voltage [V]	550	550	550
Startup voltage [V]	100	100	100
Nominal input voltage [V]	360	360	360
MPP tracker voltage range [V]	100~530	100~530	100~530
No. of MPP trackers/Strings per MPP tracker	2(1/2)	2(1/2)	2(1/2)
Max. PV input current [A]	14/28	14/28	14/28
Isc PV Array Short Circuit current [A]	18/36	18/36	18/36

AC OUTPUT

Rated AC output power [W]	6000	7000	8000
Rated AC output current [A]	26	30	34.7
Max. AC output apparent power [VA]	6600	7700	8800
Max. AC output current [A]	28.7	33.5	38.3
Nominal AC voltage/AC voltage range [V]*	220V/230/240,160~285		
Nominal AC frequency/AC frequency range [Hz]*		50/60, ±5	
Power Factor range		0.8 leading~0.8 lagging	
THDi (rated power) [%]		<3	

SYSTEM DATA

Max. efficiency [%]	97.40	97.40	97.40
Euro efficiency [%]	96.80	96.80	96.80
Standby consumption(night) [W]		<1	
Ingress protection		IP65	
Operating ambient temperature range [°C]		-25~60 (derating at 45)	
Max. operation altitude [m]		≤2000	
Relative humidity [%]		0~100 (non-condensing)	
Typical noise emission [dB]		<40	
Storage temperature [°C]		-25~60	
Dimensions (WxHxD) [mm]		401*450*190	
Weight [kg]		22	
Cooling concept		Natural cooling	
Communication interfaces		USB/RS485/DRM, Optional: Meter/CT	
Optional monitoring dongle		Pocket WiFi/LAN	
Display		LCD(16 x 2) / APP	

PROTECTION

Over/under voltage protection	YES
DC isolation protection	YES
Monitoring ground fault protection	YES
Grid monitoring	YES
DC injection monitoring	YES
Back feed current monitoring	YES
Residual current detection	YES
Anti-islanding protection	YES
Over temp protection	YES

STANDARD

Safety	IEC/EN 62109-1/-2
EMC	EN61000-6-1/2/3/4;EN61000-3-2/3/11/12
Certification	AS4777.2/EN 61000-3-2/EN 61000-3-3/EN 61000-3-11/EN 61000-3-12/EN 61000-6-1/EN 61000-6-2/EN 61000-6-3

* The AC voltage and the frequency range may vary from different country codes

V3.2. Information may be subject to modify without notice.